# Prowlarr

Prowlarr works as a proxy server

- Prowlarr

# Prowlarr

## Logging in

- Upon entering the interface, you'll be greeted with the login window. Type in your set username and password to get into the interface.

# Adding Sonarr/Radarr to Prowlarr

- In the Prowlarr UI navigate to **Settings > Apps** and add the applications you are using:

### Radarr

```
Enable: Checked
Prowlarr Server: https://{username}.{servername}.usbx.me/prowlarr
Radarr Server: https://{username}.{servername}.usbx.me/radarr
API Key: {Radarr API Key}
```

### Sonarr

```
Enable: Checked
Prowlarr Server: https://{username}.{servername}.usbx.me/prowlarr
Sonarr Server: https://{username}.{servername}.usbx.me/sonarr
API Key: {Sonarr API Key}
```

### Readarr

```
Enable: Checked
Prowlarr Server: https://{username}.{servername}.usbx.me/prowlarr
Readarr Server: https://{username}.{servername}.usbx.me/readarr
API Key: {Readarr API Key}
```

# Download Clients

## Torrent Clients

> Be sure to enable `Show Advanced settings` using the **Cog Icon** in the top left-hand side to show **URL Base** field.

## Deluge

```
Host: {username}.{servername}.usbx.me
Port: 443
URL Base: /deluge
Password: As configured in UCP under Deluge
Category: prowlarr
Add Paused: NO
Use SSL: YES
```

## rTorrent

```
Host: {username}.{servername}.usbx.me
Port: 443
URL Path: /RPC2
Username: {username}
Password: As configured in UCP under ruTorrent
Category: prowlarr
Add Stopped: NO
Use SSL: YES
```

## Transmission

```
Host: {username}.{servername}.usbx.me
Port: 443
Username: {username}
Password: As configured in UCP under Transmission
Category: prowlarr
Add Stopped: NO
Use SSL: YES
```

## qBittorrent

```
Host: {username}.{servername}.usbx.me
Port: 443
URL Base: /qbittorrent
Password: As configured in UCP under qBittorrent
Category: prowlarr
Add Paused: NO
Use SSL: YES
```

# Usenet Clients

## SABnzbd

```
Host: {username}.{servername}.usbx.me
Port: 443
URL Base: /sabnzbd
API Key: As obtained from SABnzbd
Username: {username}
Password: Configured during SABnzbd setup
Category: prowlarr
Use SSL: YES
```

## NZBGet

```
Host: {username}.{servername}.usbx.me
Port: 443
URL Base: /nzbget
Username: {nzbget username}
Password: {nzbget password}
Category: prowlarr (You may need to update this in NZBGet Settings if connection fails)
Add Paused: NO
Use SSL: YES
```